

The First and Only COMPLETE Lime Replacement

EcoSYN™ Synthetic Builders Lime

Eco-Friendly Green Product



Directions of use for EcoSYN™ Synthetic Builders Lime

Bricklaying and Rendering Mortar Mixes:

1. Add 9 to 10 litres of clean to a wheel barrow or mortar mixer.
2. Add 20kg of cement.
3. Add 150grams of EcoSYN™ for bricklaying mortar or 215grams of EcoSYN™ for rendering mortar.
4. Mix for a minimum of 2 minutes.
5. Add 16 - 18 standard shovels of washed mortar sand for bricklaying mortar or 18 - 20 standard shovels of washes plaster sand for rendering mortar.
6. Mix for a minimum of five minutes.

To achieve best workability additional water may be added "sparingly".

EcoSYN™ Synthetic Builders Lime

Makes all mortar mixes more workable, stickier, more consistent, more flexible and stronger

- Up to 50% less water needed
- Adds up to 10% more volume to every mix
- Approx. 600 grams replaces approx. a 20kg bag of builders lime
- Lime-free green patented technology
- Non-toxic, non-caustic, non-carcinogenic
- Biodegradable
- Safe for workers
- Meets the AS3700 standard
- Adds strength and flexibility to all mortar mixes
- No paint peel or burnout
- No other additives required
- Smaller and lighter product equals less shelf space, less freight costs, and easier to carry

Green Technology

Uses less water, non-toxic, non-caustic, non-carcinogenic, biodegradable and worker friendly.

Lower Costs

Reduced water costs, reduced freight costs, less wastage and adds more volume.

Better Finish

A stronger finished product without the problematic issues related to builders lime (e.g. Paint peel, cracking and chipping).

WWW.AUSMIX.NET.AU

Customer Helpline: 1300 851 944 | Fax: +61 2 9690 0122 | Email: info@ausmix.net.au
Ausmix Concrete Products Pty Ltd | A.C.N 162 450 795 | Australian Patent Pending # 2013902449

Like us on
Facebook



www.facebook.com/ecosyn.net.au